

Feelmaster

Feelux remote control system



Feelmaster

Model name	FM-IA2400
Each channel	Max 56 channel
Support controller	
WAN	1 Port, 10/100 Base-T, RJ45
LAN	1 Port, 10/100 Base-T, RJ45
WIFI	Compliant to IEEE802.11 b/g/n
Zigbee	Compliant to IEEE802.15.4
FeelNet	1 Port (DMX512/RS485), RJ45
USB	USB2.0
Size	100(W) X 100(D) X 25(H) mm
Power	DC 24V



• White

• Black

DC Decoder



Model name	FDC-L2Z
Input Voltage	DC 12V/24V
Output Voltage	DC 12V LED Max.50W (25W/CH) DC 24V LED Max.100W (50W/CH)
Input Signal	ZIGBEE
Channel	2CH
LAMP	DC 12V/24V LED
Dimension	W78 X H40 X D16

AC Decoder



Model name	FDA-P2Z
Input Voltage	AC200-240V, 50/60Hz
Rated Output	MAX 400W/CH (MAX 10pcs/CH)
Input Signal	ZIGBEE
Channel	2CH
LAMP	Dim Slim/ Dim Slim Line
Dimension	W200 X H50 X D35



Model name	FDA-L2Z
Input Voltage	DC 12V/24V
Output Voltage	DC 12V LED Max.100W (50W/CH) DC 24V LED Max.200W (100W/CH)
Input Signal	ZIGBEE
Channel	2CH
LAMP	DC 12V/24V LED
Dimension	W200 X H50 X D35



Model name	FDA-C2Z
Input Voltage	AC200-240V, 50/60Hz
Input Signal	ZIGBEE
Output Type	Control Feelux Curtain Only
Channel	2CH
Dimension	W200 X H50 X D35