

TEST REPORT

1. Applicant

* Client Name : FEELUX Co. Ltd.
 * Address : 235-48 Gwangjeok-ro Gwangjeok-myeon Yangju-si Gyeonggi-do 482-844 Korea
 * Date of Receipt : 20260324

2. Purpose of Report :

3. Number of Report : KH FEELUX

4. Test Standard / Item : / 260324 DVS4A 30K-24V-SW-WT-25-C90_F2602_VER4.03_COBL9

5. Test Period : 260324 ~ 260324

6. Test Environment

* Ambient Temp. : 25.0 +- 3 °C
 * Relative Humidity : 60.0 +- 10 % RH

7. Test Item

* Name of Product :
 * Rating :
 * Model :

8. Test Result : Refer to the attachment

Confirmation	Test by		Technical manager	
	김정도	Sign	김정도	Sign

- * The result shown in this test report refer only to the sample(s) tested unless otherwise stated.
- * This report cannot be reporduced, except in full.
- * This report is for reference only. It cannot replace the report by standard organization(s).

Result

Report Number	Sample Name	Sample Number	Test Standard
KH FEELUX			

Test Item	Unit	Result	Notice
Beam Distribution Test		See Attachement	
ATHD	%	0.0	
CIE 1931 Cx, Cy		0.4333 , 0.4055	
Correlated Color Temperature	K	3075	
Ra		93.59	
Power Factor		1.000	
Input Voltage	V	23.972	
Input Current	A	0.187	
Input Watt	W	4.4924	
Lamp Flux	lm	346.1	
Efficient	lm/W	77.04	
luminous Intensity (Max , Center)	cd	971 , 958	
Illuminance	lx	958	1 m
		240	2 m
		106	3 m

* This test result is for the sample provided by the client.

* Sample photo

[Click to load image](#)

Luminaire KH FEELUX

Lamp

Report

KH FEELUX

No. of lamps 1

Filename: 260324 DVS4A 30K-24V-SW-WT-25-C90_F2602_VER4.03_COBL9.jdt

Lamp flux (lm) 346


Operator: rent (A) 0.18748

Total flux (lm) 346

Date: Power Factor 0.9996

2026-03-24 오후 4:19:17

Luminous Intensity Distribution



Luminaire KH FEELUX

Lamp

Report

KH FEELUX

No. of lamps 1

Filename: 260324 DVS4A 30K-24V-SW-WT-25-C90_F2602_VER4.03_COBL9.jdt

Lamp flux (lm) 346


Operator: rent (A) 0.18748

Total flux (lm) 346

Date: Power Factor 0.9996

2026-03-24 오후 4:19:17

Luminous Intensity Distribution (Lowest 10%)



Total Optical Solution Provider

Luminaire KH FEELUX

Lamp		Report		KH FEELUX
No. of lamps	1	Filename	260324 DVS4A 30K-24V-SW-WT-25-C90_F2602_VER4.03_COBL9.jdt	
Lamp flux (lm)	346	Operator	rent (A)	0.18748
Total flux (lm)	346	Date	Power Factor	0.9996
				2026-03-24 오후 4:19:17

Luminous Intensity Data

Maximum (cd) : 971

Minimum (cd) : 0

G/C	0	30	60	90	120	150	180	210	240	270	300
0	958.07	971.42	960.76	936.66	902.63	894.93	958.07	971.42	960.76	936.66	902.63
10	692.58	654.38	602.33	522.13	471.18	424.31	601.68	619.96	646.82	718.86	766.91
20	245.4	240.1	220.07	185.72	163.76	149.9	211.11	226.36	248.87	286.82	317.39
30	96.81	93.88	90.25	77.88	69.95	62.11	82.71	85.54	93.48	104.18	112.99
40	42.65	41.51	40.71	36.27	32.08	29.43	37.17	36.77	38.84	42.86	45.95
50	21.64	21.05	21.49	19.09	18.28	17.02	19.95	19.12	19.62	20.53	21.74
60	11.11	11.46	11.68	10.86	10.07	9.28	11.35	11.64	11.55	11.68	12.13
70	4.85	5.44	6	4.59	5.2	4.97	6.04	5.98	6.55	7.03	7.07
80	1.98	1.83	0.77	1.96	1.56	1.15	2.07	2.72	1.91	2.82	1.63
90	0.8	0.16	0.07	-0.13	0.73	0.07	-0.07	0.39	-0.05	-0.45	0.33
100	0.22	-0.01	-0.11	0.36	0.41	0.33	0.55	0.37	-0.14	0.59	0.14
110	0	0.04	-0.16	-0.29	0.49	0.2	0.56	-0.49	0.77	0.62	0.61
120	0.45	-0.16	1.07	0.23	1.4	-0.02	0.61	0.5	-0.15	0.65	0.31
130	1.2	0.25	0.63	1.22	1.79	2.03	1.05	0.56	0.91	-0.05	1.26

Luminaire KH FEELUX

Lamp		Report	KH FEELUX
No. of lamps	1	Filename	260324 DVS4A 30K-24V-SW-WT-25-C90_F2602_VER4.03_COBL9.jdt
Lamp flux (lm)	346	Operator	rent (A) 0.18748
Total flux (lm)	346	Date	Power Factor 0.9996 2026-03-24 오후 4:19:17

Luminous Intensity Data (Continued)

Maximum (cd) : 971

Minimum (cd) : 0

G/C	330	360
0	894.93	958.07
10	825.58	692.58
20	346.73	245.4
30	122.32	96.81
40	51.51	42.65
50	24.6	21.64
60	14.07	11.11
70	7.34	4.85
80	3.27	1.98
90	0.08	0.8
100	0.94	0.22
110	0.27	0
120	-0.15	0.45
130	0.84	1.2

Luminaire KH FEELUX

Lamp		Report		KH FEELUX
No. of lamps	1	Filename	260324 DVS4A 30K-24V-SW-WT-25-C90_F2602_VER4.03_COBL9.jdt	
Lamp flux (lm)	346	Operator	rent (A)	0.18748
Total flux (lm)	346	Date	Power Factor	0.9996
				2026-03-24 오후 4:19:17

Luminous Flux Table

Total Lamp Lumens:	346.13
Luminaire Efficiency (lm/W):	77.05
CIE Classification:	Direct

Elevation	Lumens	Cumulative	Lamp %	Luminaire %
0	22.41	22.41	6.48	6.48
10	119.61	142.02	41.03	41.03
20	88.72	230.74	66.67	66.66
30	49.84	280.58	81.07	81.06
40	27.91	308.49	89.13	89.13
50	17.07	325.56	94.06	94.06
60	10.82	336.38	97.19	97.18
70	6.09	342.47	98.95	98.94
80	2.13	344.60	99.57	99.56
90	0.18	344.78	99.62	99.61
100	0.33	345.10	99.71	99.70
110	0.23	345.33	99.78	99.77
120	0.38	345.70	99.89	99.88
130	0.42	346.13	100.01	100.00

Luminaire KH FEELUX

Lamp

Report

KH FEELUX

No. of lamps 1

Filename: 260324 DVS4A 30K-24V-SW-WT-25-C90_F2602_VER4.03_COBL9.jdt

Lamp flux (lm) 346


Operator: rent (A) 0.18748

Total flux (lm) 346

Date: Power Factor 0.9996

2026-03-24 오후 4:19:17

IsoCandela (Type C)



Luminaire KH FEELUX

Lamp

Report

KH FEELUX

No. of lamps 1

Filename: 260324 DVS4A 30K-24V-SW-WT-25-C90_F2602_VER4.03_COBL9.jdt

Lamp flux (lm) 346


Operator: rent (A) 0.18748

Total flux (lm) 346

Date: Power Factor 0.9996

2026-03-24 오후 4:19:17

IsoLux Diagram (Ground)



Pole Height (m): 2.7

Area Width (m): 12

Total Optical Solution Provider

Luminaire KH FEELUX

Lamp

Report

KH FEELUX

No. of lamps 1

Filename: 260324 DVS4A 30K-24V-SW-WT-25-C90_F2602_VER4.03_COBL9.jdt

Lamp flux (lm) 346


Operator: rent (A) 0.18748

Total flux (lm) 346

Date: Power Factor 0.9996

2026-03-24 오후 4:19:17

IsoLux Diagram (Wall)



Pole Height (m): 2.7

Wall Distance (m): 2.7

Aiming Plane: 0

Wall Height (m): 12

Total Optical Solution Provider

Luminaire KH FEELUX

Lamp

Report

KH FEELUX

No. of lamps 1

Voltage (V) 23.972

Filename 260324 DVS4A 30K-24V-SW-WT-25-C90_F2602_VER4.03_COBL9.jdt

Lamp flux (lm) 346

Current (A) 0.18748

Operator

Total flux (lm) 346

Power Factor 0.9996

Date

2026-03-24 오후 4:19:17

Illuminance Levels (Ground)



6.00	0.04	0.05	0.03	0.04	0.06	0.07	0.07	0.07	0.06	0.05	0.04	0.05	0.04
5.00	0.04	0.03	0.05	0.08	0.19	0.26	0.26	0.26	0.22	0.09	0.06	0.04	0.05
4.00	0.03	0.05	0.16	0.26	0.21	0.32	0.34	0.32	0.24	0.29	0.18	0.05	0.03
3.00	0.04	0.07	0.24	0.27	0.90	0.73	0.92	0.83	1.02	0.29	0.29	0.08	0.05
2.00	0.05	0.19	0.21	0.76	1.10	2.13	3.61	2.72	1.31	1.06	0.24	0.22	0.06
1.00	0.07	0.24	0.29	0.69	2.08	9.31	57.83	12.40	2.73	0.84	0.36	0.30	0.08
0.00	0.08	0.27	0.36	0.96	3.77	66.63	131.42	76.71	4.37	1.06	0.37	0.29	0.07
-1.00	0.07	0.23	0.29	0.76	2.42	11.04	79.74	14.70	3.08	0.90	0.36	0.29	0.07
-2.00	0.06	0.21	0.24	0.93	1.17	2.43	4.57	3.01	1.34	1.25	0.25	0.24	0.07
-3.00	0.05	0.09	0.27	0.29	0.96	0.76	1.03	0.84	1.07	0.30	0.33	0.11	0.06
-4.00	0.04	0.06	0.17	0.27	0.24	0.32	0.37	0.32	0.25	0.28	0.19	0.07	0.05
-5.00	0.05	0.04	0.06	0.09	0.21	0.26	0.28	0.26	0.23	0.09	0.07	0.05	0.06
-6.00	0.04	0.05	0.04	0.05	0.07	0.08	0.09	0.08	0.07	0.06	0.04	0.05	0.04
-6.00	-5.00	-4.00	-3.00	-2.00	-1.00	0.00	1.00	2.00	3.00	4.00	5.00	6.00	

Illum. (Max.) : 131.42

Illum. (Min.) : 0.0295

Illum. (Avg.) : 3.1881

All illuminance level values are in lux.



Luminaire KH FEELUX

Lamp

Report

KH FEELUX

No. of lamps 1

Filename: 260324 DVS4A 30K-24V-SW-WT-25-C90_F2602_VER4.03_COBL9.jdt

Lamp flux (lm) 346


Operator: rent (A) 0.18748

Total flux (lm) 346

Date: Power Factor 0.9996

2026-03-24 오후 4:19:17

Illuminance Cone Diagram



Luminaire KH FEELUX

Lamp

Report

KH FEELUX

No. of lamps 1 Voltage (V) 23.972

Filename 260324 DVS4A 30K-24V-SW-WT-25-C90_F2602_VER4.03_COBL9.jdt

Lamp flux (lm) 346 Current (A) 0.18748

Operator

Total flux (lm) 346 Power Factor 0.9996

Date 2026-03-24 오후 4:19:17

Coefficient of Utilization

	Refl. Ceiling (%)	80%	80%	80%	70%	70%	70%	50%	50%	50%	30%	30%	30%	10%	10%	10%	0%
	Refl. Wall (%)	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
Eff. Floor Cavity Refl.		20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%
Room CR 0		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 1		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 2		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 3		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 4		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 5		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 6		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 7		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 8		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 9		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 10		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00